



VIVO II S Ra >80

- LED spotlight with stabilised colour temperature (warm white / neutral white)
- Optimised for efficient and high-output accent lighting in retail and automotive applications as well as architectural lighting
- 3-phase LED spotlight with converter integrated in universal adapter
- Die-cast aluminium spotlight housing
- Colour: black or white microtextured paint, other colours such as matt silver, concrete grey, chrome-colour or cooper-colour are possible as variants
- Spotlight rotatable through 360°, 337° and pivotable through 90°
- Excellent glare control via front ring made of PC, black or white, other colours such as concrete grey, chrome-colour or copper-colour are possible as variants
- Front ring accommodates the accessories (optical, protective glass, honeycomb louvre)
- Specular reflector of aluminised PC, highly specular, iridescence-free
- 50000 h service life at 80 % luminous flux
- stableWhite colour temperature: 3000 K (LED830: warm white) or 4000 K (LED840: intermediate)
- Colour rendering index: Ra > 80
- Luminaire luminous flux: 2700–2800 lm (28 W)
- Luminaire efficiency: 83–93 lm/W
- Control: switchable, dimmable Dali only as well as wireless connection via app with Bluetooth® 4.x - basicDim Wireless as variant
- Mains voltage: 220–240 V / 50/60 Hz
- Specular reflector designed to be interchangeable
- Wall mounting is not permissible; heavy-duty adapter for vertical installation as variant
- Not suitable for point outlets

Accessory

V2 S BOPT	60700415
V2 S FRONTRING BK	60700449
V2 S FRONTRING BKG	60700450
V2 S FRONTRING CRG	60700455
V2 S FRONTRING CUG	60700454
V2 S FRONTRING GYC	60700453
V2 S FRONTRING GYD	60700452
V2 S FRONTRING SM	60700451
V2 S FRONTRING WH	60700447
V2 S FRONTRING WHG	60700448
V2 S HONEYCOMB LOUVRE BK	60700416
V2 S OVAL OUTLINE LENS	60700417
V2 S PROTECTION GLASS	60700418
V2 S REFL FL	60700422
V2 S REFL MSP	60700421
V2 S REFL SP	60700420
V2 S REFL WFL	60700423
V2 S SOFT OUTLINE LENS	60700419



Designer: EOOS

