



Art.no. 300136

EAN 7320046370305



A wall luminaire with a combination of indirect light and opal surfaces that creates a soft yet functional lit accessory to a buildings facade.

Installation Luminaire for wall mounting.

Connection Connection block 3x2,5 m². Wall bracket with three fastening points. Surface mounted cable via knock-out. For connection from the rear, see dimension diagram. Through-wiring not possible.

Design Body of cast aluminium with stainless steel details. Diffuser of UV-stabilised, clear polycarbonate. Ballast integrated in the luminaire.

Designed by Tommy Govén.

Standard colour Anthracite grey. Other colours are ordered with additional suffix code: Alu-grey (RAL 9006) -236.

Azur Wall

Direct

DESIGN

Louvre Opal	Colour Anthracite grey
Weight, kg 3.4	Length, mm 258
Width, mm 190	Height, mm 230

TECHNICAL DATA

Projected wind area, m² 0.059	Protective class 2
IK rating 10	IP rating 65
Corrosion class C3	Min. ambient temperature, °C -25
Max. ambient temperature, °C 25	Brand of driver Philips

ELECTRICAL DATA

MCB B10A 30	MCB B16A 48
MCB C10A 49	MCB C16A 81
AM Yes	Rated supply voltage, V 220-240
Mains frequency, Hz 50, 60	Start W 9
Average W 9	End W 9
Power factor, 100 % 0.95	Surge protection CM, kV/kA 10
Surge protection DM, kV/kA 6	THD, % 9

LIGHTING DATA

Energy class, LED module E	Light distribution Direct
Lumen output 713	lm/W 82
Lumen maintenance L100 B50, h 50 000	Lumen maintenance 50 000 h L100
Lumen maintenance at 50 000 h 1	LED driver, h/max failure % 100000/10
CLO function on Yes	CLO time, h 50 000
SDCM 3	CRI 80
CCT, K 3000	Light source LED
Light source colour 830	