
FAGERHULT

Printed from fagerhult.com 2023-01-24

Art.no. 45100-20002

EAN 7316910723667







A rail-mounted linear luminaire with a softly rounded inner profile and 3 different light distribution patterns that meet the lighting requirements of larger stores, such as hypermarkets and department stores. The Sentra is available in 2 lengths, 1200 mm and 1800 mm.

Installation On rail Lighting Track Pro (on/off) or Control Track (DALI).

Design Frame in white (RAL 9016) or black (RAL 9005) structured lacquer.

Louvre Linear extruded lens for asymmetric and double asymmetric light distribution. Opal louvre shutters for wide light distribution.

Light distribution Asymmetrical, double asymmetrical or wide (opal).

 $\textbf{Dimming} \ \, \textbf{On-off or DALI/phase pulse}.$

Rail Lighting Track Pro or Control Track (DALI).

Adapter 3-phase adapter for Lighting Track Pro (power on/off), DALI adapter for Control Track (DALI).

LED-information 3000K or 4000K, CRI 80.

Miscellaneous CLO (Constant Light Output) in DALI versions.

Sentra

Double asymmetrical, 3-phase track, On/off

DESIGN

Louvre Lens Colour White Weight, kg 5.2 Length, mm 1814 Width, mm 105 Height, mm 96 Module 1800

TECHNICAL DATA

Installation 3-phase track Protective class 1 Min. ambient temperature, °C -25 IP rating 20

Light control On/off Max. ambient temperature, °C 25

Brand of driver Tridonic

ELECTRICAL DATA

MCB B10A 6 MCB B16A 10 MCB C10A 10 MCB C16A 16

Rated supply voltage, V 220-240

Effect, W 73

Surge protection CM, kV/kA 2

THD. % 8

Mains frequency, Hz 0, 50, 60 **Power factor, 100 %** 0.99 Surge protection DM, kV/kA 1

LIGHTING DATA

Energy class, LED module C Light distribution Double

> asymmetrical Im/W 151

Lumen output 11037 Lumen maintenance 50 000 h L91 Lumen maintenance 75 000 h L86

Lumen maintenance 100 000 h L82

LED driver, h/max failure %

100000/10 **CRI** 80

Lumen maintencance at 50 000 h 0.91

SDCM 3

CCT, K 3000