



Art.no. 65100

EAN 7320049825956



A rail-mounted, Ø 55 mm spotlight for directional light. Deep reflector for optimal light comfort and and good light distribution.

Installation Mounted on 3-phase rail or Control Track (DALI).

Connection Adapter in the rail.

Design Standard white (RAL 9016) or black (RAL 9005).

Light distribution Narrow, medium or wide light distribution.

Dimming DALI, e-Sense Stage.

Rail 3-phase rail or Control Track (DALI).

Adapter The adapter locks mechanically to the rail with a knob. Phase 1, 2 or 3 can then be selected with the phase selector knob.

LED-information Intrack driver in adapter.

Zkye 55 G2 Spotlight

Narrow Beam, 3-phase track

DESIGN

Colour White	Weight, kg 0.4
Length, mm 171	Width, mm 55
Height, mm 171	

TECHNICAL DATA

Installation 3-phase track	Turn, ° 360
Tilt, ° 90	Protective class 2
IP rating 20	Min. ambient temperature, °C -25
Max. ambient temperature, °C 25	Brand of driver Philips

ELECTRICAL DATA

MCB B10A 45	MCB B16A 72
MCB C10A 74	MCB C16A 122
Rated supply voltage, V 220-240	Mains frequency, Hz 50, 60
Effect, W 15	Power factor, 100 % 0.99
Surge protection CM, kV/kA 2	Surge protection DM, kV/kA 1
THD, % 7	

LIGHTING DATA

Energy class F	Light distribution Narrow Beam
Lumen output 1101	lm/W 75
Lumen maintenance L90 B50, h 100 000	Lumen maintenance 35 000 h L96
Lumen maintenance 50 000 h L95	Lumen maintenance 75 000 h L94
Lumen maintenance 100 000 h L93	Lumen maintenance at 50 000 h 0.95
LED driver, h/max failure % 100000/10	SDCM 2
CRI 90	CCT, K 2700
Beam angle, ° 15	