



Art.no. 84021

EAN 7320048137005



A rail-mounted, Ø 55 mm spotlight for directional light.

Installation Mounted on 3-phase rail.

Connection Adapter in the rail.

Design Standard white (RAL 9016) or black (RAL 9005).

Light distribution Narrow, medium or wide light distribution.

Adapter The adapter locks mechanically to the rail with a knob. Phase 1, 2 or 3 can then be selected with the phase selector knob.

LED-information Driver integrated in the spotlight housing for On/Off.

Zkye 55 Eco Spotlight

Narrow Beam

DESIGN

| | |
|-----------------------|-----------------------|
| Colour Black | Weight, kg 0.5 |
| Length, mm 250 | Width, mm 80 |
| Height, mm 55 | |

TECHNICAL DATA

| | |
|---|--|
| Turn, ° 360 | Tilt, ° 90 |
| Protective class 1 | IP rating 20 |
| Min. ambient temperature, °C -25 | Max. ambient temperature, °C 25 |
| Brand of driver Philips | |

ELECTRICAL DATA

| | |
|--|-------------------------------------|
| MCB B10A 21 | MCB B16A 34 |
| MCB C10A 35 | MCB C16A 59 |
| Rated supply voltage, V 220-240 | Mains frequency, Hz 50, 60 |
| Effect, W 22 | Power factor, 100 % 0.98 |
| Surge protection CM, kV/kA 2 | Surge protection DM, kV/kA 1 |
| THD, % 10 | |

LIGHTING DATA

| | |
|--|---|
| Energy class, LED module F | Light distribution Narrow Beam |
| Lumen output 1905 | lm/W 87 |
| Lumen maintenance L90 B50, h 100 000 | Lumen maintenance 35 000 h L96 |
| Lumen maintenance 50 000 h L95 | Lumen maintenance 75 000 h L94 |
| Lumen maintenance 100 000 h L93 | Lumen maintenance at 50 000 h 0.96 |
| LED driver, h/max failure % 100000/10 | SDCM 3 |
| CRI 90 | CCT, K 3000 BBBL |
| Beam angle, ° 16 | |