



Art.no. 84040

EAN 7320048135346



A Ø 55 mm pendant luminaire. Deep-recessed optics for optimal light comfort. For mounting to fixed ceilings with ceiling cups, or on contact rails with adapter.

Connection In ceiling cup: snap-in terminal block 5 x 2.5 mm².
On contact rail: adapter for 3-phase rail or Control Track (DALI).

Design Standard white (RAL 9016) or black (RAL 9005).

Light distribution Wide light distribution.

Dimming DALI, Casambi or Trailing Edge (rear edge control).

Rail 3-phase rail or Control Track (DALI).

Adapter The adapter locks mechanically to the rail with a knob. Phase 1, 2 or 3 can then be selected with the phase selector knob.

LED-information Driver integrated in luminaire housing.

Zkye 55 Pendant

Wide Beam

DESIGN

Colour White	Weight, kg 0.7
Length, mm 2800	Width, mm 70
Height, mm 70	

TECHNICAL DATA

Protective class 1	IP rating 20
Min. ambient temperature, °C -25	Max. ambient temperature, °C 25
Brand of driver Osram	

ELECTRICAL DATA

MCB B10A 38	MCB B16A 60
MCB C10A 57	MCB C16A 91
Rated supply voltage, V 220-240	Mains frequency, Hz 50, 60
Effect, W 14	Surge protection CM, kV/kA 2
Surge protection DM, kV/kA 1	

LIGHTING DATA

Energy class, LED module F	Light distribution Wide Beam
Lumen output 934	lm/W 66
Lumen maintenance L90 B50, h 100 000	Lumen maintenance 35 000 h L96
Lumen maintenance 50 000 h L95	Lumen maintenance 75 000 h L94
Lumen maintenance 100 000 h L93	Lumen maintenance at 50 000 h 0.96
LED driver, h/max failure % 100000/10	SDCM 2
CRI 90	CCT, K 2700
Beam angle, ° 32	