

The TITAN ANGLE 45° is a corner mount fitting which is designed to be comfortable and durable but still withstand violence and rough weather conditions, the product is widely used in environments which are sensitive for molest. The TITAN ANGLE series is mainly used as the main lighting in underpasses, canopies and alleys.

IP65

IK16



## Specifications

Housing material	Stainless steel and aluminium
Surface finish	Powder coated
Cover material	Polycarbonate Structured
LED type	Medium Power SMD LED
CRI	≥ 80
Voltage	230 V
Lifetime fixture	30 years
Lifetime LED	L90B10 @ 100.000h, 25°C
Dimmable	DALI
Future proof	Yes
LED efficiency	200 Lumen/Watt

 These specifications can be customized on request, please contact us for more information

Typenumber	Length	Lumen	Load	Weight
TA453 1 3K B	375mm	994 lm	6.2W	4.8 kg
TA457 1 3K B	722mm	1062 lm	6.2W	7.6kg
TA457 2 3K B	722mm	2133 lm	11.8W	7.6kg
TA4513 3 3K B	1331mm	3212 lm	18.4W	13.2kg
TA4513 4 3K B	1331mm	4228 lm	23.4W	13.2kg
TA4513 5 3K B	1331mm	6473 lm	37.9W	13.2kg

Colour white (RAL 9005)	Standard (B)
Colour black (RAL 9016)	Replace B for W
Colour grey (RAL 7035)	Replace B for G
LED Colour temperature	Replace 3K for 4K
Customized product	Call us at +31-229-472011

Warranty	10 years
Country of origin	The Netherlands
SROI	> 25% of our production
Latest development	10/02/2022
LDT/IES file	Download via website

