


# AMON WALL B A/M+S/I



<b>Part number</b>	306315
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	37 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK08 5J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Asymmetric medium reflector
<b>Lightsource lumen output:</b>	4160 lm
<b>Luminaire lumen output:</b>	2358 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	80000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	30°




## Description

Wall-mounted LED luminaire, comprising:

- Extruded aluminium profile housing, painted ISO 9227
- Extra-clear, tempered, flat glass diffuser, screen-printed inside
- High-transparency polycarbonate lenses grant an optimized light transmission
- Anti-ageing silicone gasket
- Painted die cast aluminium trims and caps
- Built-in driver
- Aluminium heat sink
- Stainless steel external screws
- Painted die cast aluminium bracket for wall mounted (WALL) applications, for easy installation
- Double emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

