

# O41

## Decorative 4 to 6 m column LED luminaire



### Description

Glamox O41 is a decorative 4 to 6 m column LED luminaire. Suitable for parks, paths and amenity lighting. The luminaire can be mounted on the wall with an accessory bracket. Available in three colours; black, anthracite or aluminium grey.

O41 is manufactured with luminaire housing in die-cast aluminium. Double layer polyester powder coated paint finish. The luminaire is available with three types of optics; Wide beam (WB), wide beam asymmetrical for pathway lighting (WBA) and medium beam asymmetrical (MBA). The luminaire has silicone gasket and screws are in stainless steel.

O41 is equipped with 6 m pre-assembled rubber cable.

# O41

## Decorative 4 to 6 m column LED luminaire



### Technical description

<b>Light source</b>	LED 2000 - 10000 lumen out Colour temperature 3000/4000 K, CRI Ra 80, MacAdams 3	<b>Connection</b>	Supplied with 6 m pre-assembled rubber cable.
<b>Driver</b>	Fixed output (HF) or DALI dimmable (10-100%).	<b>Optic</b>	Wide beam (WB), wide beam asymmetrical for pathway lighting (WBA) and medium beam asymmetrical (MBA).
<b>Body material &amp; colour</b>	Housing in die-cast aluminium. Double layer black (RAL 9005), anthracite (close to RAL 7024) or aluminium grey (RAL 9006) polyester powder coated paint finish. Tempered safety glass cover. Silicone gasket. Screws made of stainless steel.	<b>Wind exposed surface</b>	0.09 m <sup>2</sup>
<b>Mounting</b>	On 4 to 6 m pole with top diameter of 60 mm or on the wall by use of a bracket that has to be ordered separately.	<b>Protection against surges</b>	Up to 6kV.
<b>Accessories</b>	Wall bracket	<b>Light management</b>	This product is available with Glamox NightDim.  For more information see "Light control for outdoor lighting" under "Light Management".

### Measurement drawings

